

## Assembly Numbers

### Standard Burner Assemblies

Configured Item Number	Description
.5 EI XF STR	6" straight CROSSFIRE, end inlet
1 EI XF STR	1' straight CROSSFIRE, end inlet
1.5 EI XF STR	1.5' straight CROSSFIRE, end inlet
2 BI XF STR	2' straight CROSSFIRE, back inlet
3 BI XF STR	3' straight CROSSFIRE, back inlet
4 BI XF STR	4' straight CROSSFIRE, back inlet
5 BI XF STR	5' straight CROSSFIRE, back inlet
6 BI XF STR	6' straight CROSSFIRE, back inlet
7 BI XF STR	7' straight CROSSFIRE, back inlet
8 BI XF STR	8' straight CROSSFIRE, back inlet
9 BI XF STR	9' straight CROSSFIRE, back inlet
2 BI XF GRD	2' grid CROSSFIRE, back inlet
3 BI XF GRD	3' grid CROSSFIRE, back inlet
4 BI XF GRD	4' grid CROSSFIRE, back inlet
5 BI XF GRD	5' grid CROSSFIRE, back inlet
6 BI XF GRD	6' grid CROSSFIRE, back inlet
7 BI XF GRD	7' grid CROSSFIRE, back inlet
8 BI XF GRD	8' grid CROSSFIRE, back inlet
9 BI XF GRD	9' grid CROSSFIRE, back inlet
4 BI XF LDR	4' ladder CROSSFIRE, back inlet
5 BI XF LDR	5' ladder CROSSFIRE, back inlet
6 BI XF LDR	6' ladder CROSSFIRE, back inlet
7 BI XF LDR	7' ladder CROSSFIRE, back inlet
8 BI XF LDR	8' ladder CROSSFIRE, back inlet
9 BI XF LDR	9' ladder CROSSFIRE, back inlet

Segment choices are as follows for the configured item numbers:

- Fuel
- Gas Connection
- Body Material
- Housing Material
- Air Connector
- Air Connector Material
- Cross Member Span (Grids only)
- Cross Member (Ladders only)
- End Plate
- End Mounting Bracket
- Maximum Firing Rate
- To be used with SMARTFIRE
- Customer Number
- Burner Capacity
- Lifting Lugs

Descriptions of segment choices and available options are listed on pages 5600-A/P-2 through 5600-A/P-4.

*Please furnish a sketch when ordering any CROSSFIRE assembly. This includes straight, grid, and ladder assemblies. Indicate the position of the pilot end plate on all assemblies. In addition, indicate the position of the end gas inlet if ordering the 6", 1', or 1.5' straight CROSSFIRE assembly. Sample configurations appear on pages 5600-A/P-5, 5600-A/P-6 and 5600-A/P-7.*

Distributed by:



888.858.3647 | relevantsolutions.com

## Assembly Numbers

### Segment Choice Details

Segment Name	Segment Description	Segment Choices (DEFAULT is shaded)	Segment Choice Description
FUEL	Type of fuel	BUT	Butane Gas
		<b>NAT</b>	Natural Gas
		PROP	Propane Gas
GAS CONNECTION	Type of gas inlet connection	<b>ANSI_THRD</b>	ANSI Threaded
		ISO_THRD	ISO Threaded
BODY MATERIAL	Type of body material used	CTD	Coated
		<b>STD</b>	Standard
HOUSING MATERIAL	Type of housing material used	SS	Stainless Steel
		<b>STD</b>	Standard
AIR CONNECTOR Square air inlet not available for .5', 1', and 1.5' sections.	Type, if any, of air connector	NONE	No Connector (Customer Supplied)
		SQ	6.524" x 7.503" Square
		<b>RD</b>	8" Round
AIR CONNECTOR MATERIAL	Type of material of air connector, if any	NONE	No Material
		SS	Stainless Steel
		<b>STD</b>	Standard
CROSS MEMBER SPAN (GRID ONLY)	Spacing, in feet, between cross member centerlines	<b>1</b>	12" Span
		1.5	18" Span
		2	24" Span - 1 Air
		2.5	30" Span - 1 Air
		3	36" Span - 1 Air & Gas
		4	48" Span - 1 Air & Gas
CROSS MEMBER (Quantity & Spacing) (LADDER ONLY)	Quantity and centerline spacing, in feet, of cross members	<b>112</b>	Qty 1 - 12" Spacing
		212	Qty 2 - 12" Spacing
		312	Qty 3 - 12" Spacing
		412	Qty 4 - 12" Spacing
		118	Qty 1 - 18" Spacing
		218	Qty 2 - 18" Spacing
		318	Qty 3 - 18" Spacing
		418	Qty 4 - 18" Spacing
		124	Qty 1 - 24" Spacing
		224	Qty 2 - 24" Spacing
		324	Qty 3 - 24" Spacing
		424	Qty 4 - 24" Spacing
		130	Qty 1 - 30" Spacing
		230	Qty 2 - 30" Spacing
		330	Qty 3 - 30" Spacing
		430	Qty 4 - 30" Spacing

## Assembly Numbers

**Segment Choice Details (continued)**

Segment Name	Segment Description	Segment Choices (DEFAULT is shaded)	Segment Choice Description
END PLATE (POS 1)*	Type of end plate used in position 1	PLN	Plain End Plate
		<b>PILT</b>	Standard Piloted End Plate
END PLATE (POS 2)*	Type of end plate used in position 2	<b>PLN</b>	Plain End Plate
		PILT	Standard Piloted End Plate
END PLATE (POS 3)*	Type of end plate used in position 3	<b>PLN</b>	Plain End Plate
		PILT	Standard Piloted End Plate
END PLATE (POS 4)*	Type of end plate used in position 4	<b>PLN</b>	Plain End Plate
		PILT	Standard Piloted End Plate
END MOUNTING BRACKET	Number of end mounting brackets required	(QUANTITY)	(Optional)
MAXIMUM FIRING RATE	Maximum rate per foot at which burner operates	1	1 MMBtuh/ft
		1.25	1.25 MMBtuh/ft
		1.5	1.5 MMBtuh/ft
		1.75	1.75 MMBtuh/ft
		<b>2</b>	2 MMBtuh/ft
		2.25	2.25 MMBtuh/ft
TO BE USED WITH SMARTFIRE	Is CROSSFIRE to be used with optional Maxon SMARTFIRE?	<b>NO</b>	SMARTFIRE Not Used
		YES	SMARTFIRE Used
CUSTOMER NUMBER	Attach customer number to burner?	(to be filled in)	(Optional)
BURNER CAPACITY (MMBTUH)	Capacity of burner (based on firing rate and burner length) No user input required for this field	(calculated)	---
LIFTING LUGS	Quantity and location to be specified on order	(QUANTITY)	(Optional)

**\*Denotes secondary segment choices involved (see next page)**

## Assembly Numbers

### Secondary Segment Choice Details for Standard Piloted End Plates

Segment Name	Segment Description	Segment Choices (DEFAULT is shaded)	Segment Choice Description
MATERIAL	Type of end plate material	SS	Stainless Steel
		<b>STD</b>	Gray Iron
CONNECTION	Type of connection for end plate	<b>ANSI_THRD</b>	ANSI Threaded
		ISO_THRD	ISO Threaded
GAS MIXER	Optional gas mixer	NO	Choice Not Selected
		<b>YES</b>	Choice Selected
PILOT ADJUSTABLE ORIFICE	Optional adjustable orifice for pilot	NO	Choice Not Selected
		<b>YES</b>	Choice Selected
IGNITOR	Type of ignitor required	<b>FTISS</b>	Feed Thru Ignitor w/SS Tube (available in 12", 18", 24", 30", 36", 42", 48")
		NONE	Ignitor Customer Provided
		STD	Std Ignitor w/o Feed Thru Plate
		STDP	Std Ignitor w/Feed Thru Plate
FLAME DETECTION	Type of flame detection required	NONE	No Detector Provided
		<b>UV</b>	Set Up For UV (Customer Provided)
SEAL PLATE KIT (ship loose)	Optional seal plate kit	<b>NO</b>	Choice Not Selected
		YES	Choice Selected
HOUSING MATERIAL	Choice of housing material	SS	Stainless Steel
		<b>STD</b>	Carbon Steel

### Secondary Segment Choice Details for Plain End Plates


Segment Name	Segment Description	Segment Choices (DEFAULT is shaded)	Segment Choice Description
MATERIAL	End plate material	SS	Stainless Steel
		<b>STD</b>	Carbon Steel
TYPE	Type of end plate (no user choices available)	<b>PLN</b>	Plain
HOUSING MATERIAL	Choice of housing material	SS	Stainless Steel
		<b>STD</b>	Carbon Steel

### Miscellaneous Items & Accessories

Gas mixer sub-assembly		19298
Pilot adjustable orifice	Air	15726
14mm x .875" spark ignitor		1046629
Long Shrouded Ignitor	12" long	1050342
	18" long	1050343
	24" long	1050344
	30" long	1050345
	36" long	1050346
	42" long	1050347
	48" long	1050348
Ignition Adapter		1047215

# Assembly Numbers

## CROSSFIRE® – Straight Assembly



### Standard Burner Assemblies

Configured Item Number	Description
.5 EI EX STR	6" straight CROSSFIRE, end inlet
1 EI XF STR	1' straight CROSSFIRE, end inlet
1.5 EI XF STR	1.5' straight CROSSFIRE, end inlet
2 BI XF STR	2' straight CROSSFIRE, back inlet
3 BI XF STR	3' straight CROSSFIRE, back inlet
4 BI XF STR	4' straight CROSSFIRE, back inlet
5 BI XF STR	5' straight CROSSFIRE, back inlet
6 BI XF STR	6' straight CROSSFIRE, back inlet
7 BI XF STR	7' straight CROSSFIRE, back inlet
8 BI XF STR	8' straight CROSSFIRE, back inlet
9 BI XF STR	9' straight CROSSFIRE, back inlet

### Segment choices are as follows for the configured item numbers:


- Fuel
- Gas Connection
- Body Material
- Housing Material
- Air Connector
- Air Connector Material
- End Plates
- End Mounting Bracket
- Maximum Firing Rate
- To be used with SMARTFIRE
- Customer Number
- Burner Capacity
- Lifting Lugs

***Please furnish a sketch when ordering straight assemblies.***

# Assembly Numbers

## CROSSFIRE® – Grid Assembly

3 ft. span between cross members, 1 air & gas



### CROSSFIRE® Grid Assemblies

Configured Item Number	Description
2 BI XF GRD	2' grid CROSSFIRE, back inlet
3 BI XF GRD	3' grid CROSSFIRE, back inlet
4 BI XF GRD	4' grid CROSSFIRE, back inlet
5 BI XF GRD	5' grid CROSSFIRE, back inlet
6 BI XF GRD	6' grid CROSSFIRE, back inlet
7 BI XF GRD	7' grid CROSSFIRE, back inlet
8 BI XF GRD	8' grid CROSSFIRE, back inlet
9 BI XF GRD	9' grid CROSSFIRE, back inlet


Segment choices are as follows for the configured item numbers:

- Fuel
- Gas Connection
- Body Material
- Housing Material
- Air Connector
- Air Connector Material
- Cross Member Span
- End Plates
- End Mounting Bracket
- Maximum Firing Rate
- To be used with SMARTFIRE
- Customer Number
- Burner Capacity
- Lifting Lugs

*Please furnish a sketch when ordering grid assemblies.*

## Assembly Numbers

### 9 ft. CROSSFIRE® Ladder Back Inlet with (2) cross members at 30" spacing



#### Segment choices are as follows for ladder assemblies:

- Fuel
- Gas Connection
- Body Material
- Housing Material
- Air Connector
- Air Connector Material
- Cross Member
- End Plates
- End Mounting Bracket
- Maximum Firing Rate
- To be used with SMARTFIRE
- Customer Number
- Burner Capacity
- Lifting Lugs

#### CROSSFIRE® Ladder Assemblies

Configured Item Number	Description
4 BI XF LDR	4' ladder CROSSFIRE, back inlet
5 BI XF LDR	5' ladder CROSSFIRE, back inlet
6 BI XF LDR	6' ladder CROSSFIRE, back inlet
7 BI XF LDR	7' ladder CROSSFIRE, back inlet
8 BI XF LDR	8' ladder CROSSFIRE, back inlet
9 BI XF LDR	9' ladder CROSSFIRE, back inlet

**NOTE:** Larger burners may need to be ordered and/or shipped in segments (for ladder assemblies only). Contact Maxon for details.

**Please furnish a sketch when ordering ladder assemblies.**

# Notes