

Trio™ Q

Licensed UHF

Ethernet and Serial data radio

QP450 – Hot Standby Half Duplex



Distributed by:



888.858.3647 | relevantsolutions.com



Trio Q Data Radios are advanced, high-speed licensed digital data radios, providing both Ethernet and serial communications for complex and demanding applications in Point-to-Point and Point-to-Multipoint (Multiple Address Radio) Telemetry and remote SCADA systems.

Features such as ChannelShare+™ and web-based user configuration, together with powerful remote diagnostics and Network Management, make Trio Q Data Radios the complete licensed radio solution that works with leading host systems and remote equipment.

Combining both Ethernet and serial connectivity, Trio Q Data Radios are suitable for use with the latest SCADA technology as well as providing a smooth transition from serial-based infrastructure to IP/Ethernet.

Complimenting the QR450 half duplex remote radio, the QP450 half duplex radio is ideal for deployment at base & repeater sites in systems using single frequency (simplex) operation. In high duty cycle applications, the QP450 delivers maximum rated transmitter power in ambient temperatures up to +70°C (158°F).

Product Data Sheet Trio QP450

Specifications



Trio QP450

Radio

Frequency Range	400-450MHz (L-Band) or 450-518MHz (H-Band)
Frequency Splits	Various Tx/Rx frequency splits - configurable
Channel Selection	3.125kHz channel steps
Channel Spacing	12.5 and 25kHz (software selectable)
Frequency Accuracy	±0.5ppm, -40 to +70°C (-40 to 158°F) ambient
Aging	<= 1ppm/annum
Radio Modes	Simplex or Half duplex

Transmitter

Tx Power	0.05 to 10W (+17 to +40dBm) +/- 0.1dB configurable with over-temperature and high VSWR protection
Modulation	Narrow band 2, 4, 8 and 16-level continuous phase modulation
Tx Keyup Time	<1ms
Timeout Timer	Configurable 0 to 255 seconds
Tx Spurious	<= -37dBm
PTT Control	Auto (Data)

Receiver

AFC Tracking	Digital receiver frequency tracking
Mute	Configurable digital mute

Connections

Serial Interface 1/2	1 x DB9 female connector providing 2 x RS-232 3-wire serial ports or 1x RS485 serial port (shared connector).
Serial Interface Speeds	From 600bps up to 115,200bps
Serial Interface Flow Control	Configurable hardware / 3-wire interface
Serial Interface DCD Control	Configurable DCD operation : activated on RF carrier or from user data output
Ethernet Port	3 x RJ45: 10/100 Mbps (auto-MDIX sensing) compliant with IEEE 802.3
Antenna	Refer to diagram at end of datasheet for detailed information - 2 x N female bulkhead (Refer Option B) - 1 x N female bulkhead (Refer Option E)
Power	10-pin locking, mating connector (11-30 V DC)
LED Display	Multimode Indicators for DC Power, Transmit, Receive, Synchronised Data, Serial Interface 1 & 2 Transmit & Receive Data, Ethernet 1 & 2 Transmit & Receive Data

Ethernet

Supported Protocols	Ethernet (including UDP, TCP, DHCP, ARP, ICMP, STP, IGMP, SNMP & TFPT)
Ethernet Repeating	Automatic Peer to Peer repeating
Operating Modes	Layer-2 Ethernet Bridge mode / Layer-3 IP Router mode
Ethernet Traffic Filtering	Configurable: No Filtering / Unicast Traffic & ARP Only / Unicast Traffic Only / List of approved MAC addresses
Compression	Automatic data compression
Terminal Server	Legacy RS-232/RS-485 serial support via embedded terminal server (UDP/TCP)
IP Configuration	Auto (DHCP) and Manual
SNMP	SNMP V1,V2c, RFC 1213-compliant & radio diagnostics parameters (with notifications)
Modbus Gateway	Configurable MODBUS/TCP to MODBUS/RTU Gateway
Time Server	NTP Client / Server / Client-Server / Manual modes

Specifications continue on the next page

Product Data Sheet Trio QP450

Specifications

> Trio QP450				
Modem				
RF Channel Data Rate ¹	Regulatory Region	Bandwidth (KHz)	Speed (Kbps)	RF 1x10 ⁻⁶ BER Sensitivity (dBm)
	FCC/IC	12.5	8	-113
			16	-110
			24	-107
			32	-100
	ACMA/ETSI	12.5	8	-113
16			-110	
24			-107	
32			-100	
25		14	-111	
		28	-109	
		42	-106	
		56	-99	
Dynamic Speed Selection	QoS/RSSI based Automatic Speed Selection or Fixed speed mode			
Operating Modes	Base, remote, repeater or store 'n' forward			
Collision Avoidance	Channelshare+™ - Advanced dynamic supervisory collision avoidance system Carrier Sense - Carrier sense based collision avoidance system			
Backward Compatibility ²	Backward compatible with Trio E-Series radios			
Firmware	Local and over-the-air flash-based firmware upgradable patches with support for broadcast updates			
Security				
Encryption ³	256-bit AES			
HTML Interface	Password Protected HTTP and HTTPS configuration and management interface			
Console Interface	Password protected Telnet, SSH and Serial console interface			
Password Protection	Password protected configuration sessions			
Hot Standby				
Change-over control	Manual (front panel switch) / automatic upon alarm / automatic upon timer / remote (software driven)			
Alarm Monitoring	Transmitter / General Alarms / Power Supply			
Diagnostics				
Diagnostics Overview	<ul style="list-style-type: none"> • Network management and diagnostic Windows GUI software • Network-wide operation from any remote terminal • Non intrusive protocol – runs simultaneously with the application • Storage of data error and channel occupancy statistics • Embedded Error Rate testing capabilities • Diagnostics parameters available <ul style="list-style-type: none"> • Transmitter Power • Received Signal Strength • DC Supply Voltage • Received Frequency Offset • Radio Temperature • VSWR 			
Logging	Embedded event and performance logs including time stamped data statistics and channel occupancy			
Diagnostics & Configuration	Configuration via embedded HTTP, HTTPS web interface & or Telnet/SSH/Serial console			
Ping Tester	Embedded ping test facility			
Specifications continue on the next page				

Product Data Sheet Trio QP450

Specifications



Trio QP450

General

Operating Temperature Range	-40 to +70°C (-40 to 158°F) ambient
Cooling	Built in temperature controlled fan
Input Voltage	11-30V DC
Input Power (Tx typical)	55 W @ 30dBm, 71 W @ 37dBm, 85 W @ 40dBm
Input Power (Rx typical)	14W
Housing & Dimensions	19" (483mm) 1 RU rack mount. Without mounting brackets, D:424 x H:44.45 x W:436.5mm (D:16.7" x H:1.75" x W:17.18")
Weight	5kg (11lbs.)
Warranty	3 years on parts and labor

Approvals and Certifications

Europe (ETSI)	ETSI EN 300 113, EN 301 489, EN 60950
United States (FCC)	FCC PART 15, PART 90
Canada (IC)	IC RS119, ICES-001
Australia (ACMA)	ACMA AS4295-1995 (Data)

Product Data Sheet Trio QP450

Model Code

TBURQP4HN-E00E1L0B represents a typical part number

Model	Trio Radio QB450
TBURQ	Q Data Radios
Code	Select: Unit Type
P	Half Duplex Hot Standby Radio - 19" 1RU
Code	Select: Generic Frequency Band
4	UHF: 400 - 518 MHz Band
Code	Select: Sub Band - UHF
L	Low Band : 400 to 450MHz
H	High Band : 450 to 518MHz
Code	Select: Reserved for future use
N	Reserved for future use
Code	Select: Regulatory Region¹
E00	ETSI/ACMA Region
F00	FCC Region
Code	Select: Encryption³
E	256-bit AES encryption (standard)
N	No encryption
Code	Select: Licensed Feature
1L	Ethernet & Serial (Two Ethernet & two Serial Ports)
Code	Select: Power Supply
0	10 - 30V DC
Code	Select: Hot Standby Options
B	Duplicated Tx/Rx Ports
E	Common switched Tx/Rx Port

Example: TBURQP4LN-E00E1L0B specifies: Trio QP450 Hot Standby half duplex radio, 400 to 450MHz, ETSI/ACMA Regulatory Region, 256 bit Encryption enabled, three Ethernet & two Serial Ports, 11-30V DC power supply, Duplicated Tx/Rx Ports.

Radio Regulatory Standards:

FCC – Federal Communications Commission
 IC – Industry Canada
 ETSI – European Telecommunication Standards Institute
 ACMA – Australian Communications and Media Authority

Note 1: Availability of radio models is dependent on country of deployment. Local and regulatory conditions may determine the performance and suitability of the radio in different countries. It is the responsibility of the buyer to ensure the radio model meets the regulatory conditions required. Contact your local Schneider Electric sales office for more details.

Note 2: Backward compatibility is not available for all types & models of Trio E radio. Not all features are available when operating in backward compatible mode. Contact your local Schneider Electric sales office for more details.

Note 3: Export and import restrictions may apply.

Note 4: Other country and radio regulatory regional approvals are available upon request. Contact your local Schneider Electric sales office for more details.

Disclaimer: Not all product features are available in every mode of operation. Schneider Electric reserves the right to change product specifications. For more information visit www.schneider-electric.com.


Product Data Sheet Trio QP450 Dimensions and Options

QP450 - Hot Standby Half Duplex Radio - Dimensions



QP450 - Hot Standby Half Duplex Options


Hot Standby Options



B



E

 RELAY (Coaxial Transmitter Switch)

QP450 Hot Standby Option Descriptions

	Description	Antenna Type
B	Duplicated Tx/Rx Ports	Duplicated Tx/Rx Antennas
E	Common Switched Tx/Rx Port	Common Tx/Rx Antenna