

High Speed Electric Actuators

MODEL	OUTPUT TORQUE	SPEED (60Hz)	TORQUE Switch Setting
WE-690HS2	290 In-Lbs	4.5 seconds	N/A
WE-690HS1	400 In-Lbs	7 seconds	N/A
WE-1350HS2	840 In-Lbs	7 seconds	1350 In-Lbs
WE-1350HS1	1200 In-Lbs	10.5 sec	1350 In-Lbs
WE-2640HS2	1390 In-Lbs	8.5 sec	2640 In-Lbs
WE-2640 HS1	2050 In-Lbs	13 sec	2640 In-Lbs
WE-4400HS2	2350 In-Lbs	8.5 sec	4400 In-Lbs
WE-4400HS1	3500 In-Lbs	13 sec	4400 In-Lbs
WE-6900HS2	4500 In-Lbs	10.5 sec	6900 In-Lbs
WE-10500HS1	6700 In-Lbs	15.5 sec	10,500 In-Lbs
WE-17500HS2	12000 In-Lbs	31 sec	17,500 In-Lbs
WE-25900HS1	18,000 In-Lbs	47 sec	25,900 In-Lbs

Motor specifications remain the same.

Distributed by:



Relevant Solutions | 888-858-3647 | relevantsolutions.com